DECLARATION OF PERFORMANCE NO 04CE/BIa/CSE/04

1. The unique identification code of the product type: **04/BIa/GL/CSE**
2. Intended use or use:
   Dry-pressed ceramic tiles with low water absorption E_b≤0,5%; Annex G; Bla group, glazed (GL), polished Gres Porcellanato; for interior walls and floors and exterior walls of buildings - as described on the packaging.
3. System(s) of assessment and verification of constancy of performance: ***SYSTEM 4***
4. Harmonised standard: **EN14411:2012**
5. Declared performance:

Essential characteristics	***Performance (level and/or class)***	***Harmonised technical specification***
Reaction-to-fire performance	*$A1_{FL}$*	*Classified Without Testing (CWT)*
Release of dangerous substances:		EN 14411:2012
- Cadmium	*Max 0,07mg/dm²*	
- Lead	*Max 0,8mg/dm²*	
Breaking strength:		
- thickness ≥7,5mm	*≥ 1300N*	
- thickness <7,5mm	*≥ 700N*	
Bond strength/adhesion [N/mm2]:		
- cementitious adhesives	*NPD - No Performance Determined*	
- dispersion adhesives		
- reaction resin adhesives		
- mortar		
Slippage according to CEN/TS 16165:2012, Annex B	*NPD - No Performance Determined*	
Thermal shock resistance	*Meets*	
Durability for:		
- internal use:	*Meets*	
- external use: resistance to freeze-thaw cycles	*Meets*	
Tactility	*NPD - No Performance Determined*	

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Signed on behalf of the manufacturer:

QUALITY SYSTEM MANAGER
Jolanta Grzebna