

**HANDMADE**  
2" · 10" / 5 · 25 cm



**HANDMADE**  
2" · 10" / 5 · 25 cm  
· Snow 50%  
· Duck Egg 50 %

**Available colours**  
Couleurs disponibles



Snow



Nude



Duck Egg



Sage



Cloud

**8 different reliefs**  
8 relieves diferentes

#### WAREHOUSING

In order to guarantee the characteristics of the finish the product must be kept in its original packaging until the time of fixing. If the product is likely to be stored for a long period of time it should be suitably covered.

#### TILE FIXING

To ensure the products adhere correctly to the surface, it is essential to use specific adhesive and grouting material. This must also be suitable for the environment they will have to withstand. Fitting with traditional mortars does not ensure good adhesion.

All types of joints must be planned and carried out correctly: structural, perimeter, expansion and installation joints. Fitting tiles without joints is not advisable from any technical point of view as this may lead to various problems. We recommend a minimum installation joint of 2 mm (0,079 in).

#### MAINTENANCE AND CLEANING

Once the materials have been fitted, it is advisable to remove any remaining adhesive and grouting material by using a commercial descaling product designed especially, diluted with water. The descaling product must not remain in contact with the surface to be cleaned for more than 5 minutes.

As a general guideline, powder detergents should not be used, not wire wool or abrasive materials. Generally a sponge will be sufficient with warm water and liquid neutral soap. Then rinse with plenty of clean water.

#### ALMACENAMIENTO

Para garantizar las características de su acabado, el producto debe mantenerse en su embalaje original hasta el momento de la colocación. Si el producto va a permanecer almacenado durante un largo periodo es conveniente hacerlo bajo cubierta.

#### COLOCACIÓN

Para garantizar una buena adhesión al soporte es necesaria la utilización de materiales de agarre y de rejuntado adecuados al ambiente al que vayan a estar sometidos. La colocación con morteros tradicionales no garantiza una buena adhesión.

Deberán planificarse y ejecutarse correctamente todo tipo de juntas: estructurales, perimetrales, de dilatación y de colocación. La colocación sin juntas es desaconsejable desde cualquier punto de vista técnico, pudiendo ser el origen de diversas patologías. Se recomienda una junta de colocación de 2 mm.

#### MANTENIMIENTO Y LIMPIEZA

Finalizada la puesta en obra se recomienda eliminar los restos de materiales de agarre y rejuntado con un desincrustante comercial diseñado expresamente para baldosas cerámicas, rebajado con agua, permaneciendo en contacto con la superficie a limpiar no más de 5 minutos.

Como norma general no deben utilizarse detergentes en polvo ni estropajos metálicos o abrasivos. Generalmente será suficiente con una esponja, agua tibia y un jabón líquido neutro. Posteriormente aclarar con abundante agua limpia.

Modelo/ Model	Tamaño/ Size (cm)	Piezas/Caja Pieces/Box	kg/Caja kg/ Box	m²/ Caja sqm / Box	cajas/Palet Boxes/ Pallet	m²/Palet sqm/ Pallet
Brick	5x25	48	9,79	0,573	96	55,008
Handmade	5x25	48	9,93	0,573	96	55,008
Handmade	5x50	24	10,01	0,575	88	50,600
Handmade	7,5x15	38	7,23	0,428	144	61,632
Handmade Decor B&W	7,5x15	38	7,23	0,428	144	61,632
Handmade	7,5x30	19	6,98	0,428	144	61,632
Handmade Decor Vintage	7,5x30	19	6,98	0,428	144	61,632
Bullnose	3,5x15	36	3,22	5,400 m	350	1.890 m
Bullnose	3,5x30	18	3,22	5,400 m	350	1.890 m
Rounded Edge	1,1x25	10	0,35	2,500 m	-	-
Rounded Edge Corner	1,1x1,1x1,1	-	-	-	-	-

Modelo/ Model	Tamaño/ Size (in)	Piezas/Caja Pieces/Box	lb/Caja lb/ Box	sq ft/Caja sq ft/ Box	cajas/Palet Boxes/ Pallet	sq ft/Palet sq ft/ Pallet
Brick	2x10	48	21,57	6,168	96	592,128
Handmade	2x10	48	21,90	6,168	96	592,128
Handmade	2x20	24	22,06	6,189	88	544,632
Handmade	3x6	38	15,94	4,750	144	684,000
Handmade Decor B&W	3x6	38	15,94	4,750	144	684,000
Handmade	3x12	19	15,38	4,750	144	684,000
Handmade Decor Vintage	3x12	19	15,38	4,750	144	684,000
Bullnose	1,5x6	36	7,09	18 Lft	350	6.300 Lft
Bullnose	1,5x12	18	7,09	18 Lft	350	6.300 Lft
Rounded Edge	0,43x10	10	0,77	8,202 Lft	-	-
Rounded Edge Corner	0,43x0,43x0,43	-	-	-	-	-

Technical features for Dry-Pressed ceramic tiles with water absorption BIII ( $E_b > 10\%$ ) Características técnicas para las baldosas cerámicas prensadas en seco del grupo BIII ( $E_b > 10\%$ )		
FEATURES / CARACTERÍSTICAS	SPECIFICATION / ESPECIFICACIÓN	NORMA
Dimensional Features	74.0 mm +/- 0.75 mm x 149.5 mm +/- 0.5% x 10 mm 74.0 mm +/- 0.75 mm x 300 mm +/- 0.5% x 10 mm 48.0 mm +/- 0.75 mm x 248 mm +/- 0.5% x 10 mm 48.0 mm +/- 0.75 mm x 500 mm +/- 0.5% x 10mm	UNE-EN ISO 10545-2:1998
Water absorption	$E_b > 10\%$	UNE-EN ISO 10545-3:1997
Modulus of rupture	Thickness $\geq 7,5$ mm mínimo 12 N/mm <sup>2</sup> Thickness $< 7,5$ mm mínimo 15 N/mm <sup>2</sup>	UNE-EN ISO 10545-4:2012
Crazing resistance	Pass	UNE-EN ISO 10545-11:1997
Household products resistance.	GA	UNE-EN ISO 10545-13:1998
Chemical resistance	GHA	UNE-EN ISO 10545-13:1998
Stain resistance	Class 5	UNE-EN ISO 10545-14:1998

